

VHC DC 040 SLIM

DC cross flow heat exchangers
- with low power consumption.

MAIN FEATURES

Cooling performing range: 30-150 W/K / 17-83 W/F

Equipped with advanced controller platform

Closed loop heat exchangers

Temperature range: -40 to +55 °C / -40 to +131 °F

STANDARDS

IP65 (IEC60529)

Telcordia GR-487 capable

Shock and Vibration capable ISTA-3B

RoHs/REACH/CLP

Fire resistance UL 94V

OPTIONAL FEATURES

Material: SGCC, aluminium, stainless steel

Several colours and finishes

NEMA 4 Rating

Customer control parameter settings

Self-test functionality

Recessed mounting

UNIT DESIGN

Aluzinc Steel

Powder-coated in RAL 9016

Epoxy coated heat exchanger core

External mounting

Multiple options and configurations available

CONTROLS

Fan speed controller with alarm output

RS485 communication interface

Display for setpoint adjustments

Password protected

User-friendly interface w/ display

VHC DC 040 SLIM

Technical specifications

STANDARD CONFIGURATION

GR 487 Seismic Zone 4 capable

GR 487 Salg Fog Resistance Capable

Modbus communication interface

DIMENSIONS

Height	mm	602	inch	23,7
Width	mm	305	inch	12,0
Depth	mm	175	inch	6,9
Weight	kg	13,5	lbs	30

Electrical Data

Voltage (Nominal)	V	48
Voltage (Operating range)	V	36-60 DC
Current (35°C/35 95°F/95°F)	A	1,5
Power Consumption (35°C/35°C 95°F/95°F)	W	72

Controls

Temperature Control Method	Precision Temp. Control
Fan Drive	Variable speed

VHC DC 040 SLIM

Technical specifications

COOLING PERFORMANCE

Cooling capacity (Nominal)	W/K	40	W/F	22
Cooling capacity (15°C temp. dif.)	W	600	BTU/h	2.047
Internal airflow (Actual)	M ³ /h	250	CFM	147
External airflow (Actual)	M ³ /h	250	CFM	147

AMBIENT TEMPERATURE RANGE

Maximum	°C	-40	°F	+5
Minimum	°C	+55	°F	+131
Extended operation range (min)	°C	-40	°F	-40
Extended operation range (max)	°C	+55	°F	+131

ENVIRONMENTAL INFORMATION

EER (L35/L35)

— °C	W / W	8,3
— °F	BTU/h /W	28,4

NOISE LEVEL

— Day	dB(A)	64
— Night	dB(A)	64